



Notified body No. 1121 Warrington Certification Limited, Holmesfield Road, Warrington, Cheshire, WA1 2DS, UK

# Certificate of constancy of performance 1121-CPR-AD5249

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

### ASSA ABLOY DC120 Overhead door closer

Intended use: For use on fire rated single leaf and double leaf doors STANDARD DOOR MOUNT PULL SIDE APPLICATION.

| Essential characteristics       | OUNT PULL SIDE APPLICATION  Performance           | Harmonised technical specification |  |
|---------------------------------|---|------------------------------------|--|
|                                 |   |                                    |  |
|                                 | Test Ref's :<br>WIL 358124, ATL-12-005 & PX04672A |                                    |  |
| Self closing                    | ,           |                                    |  |
| 5.2.1 General                   |   |                                    |  |
| 5.2.2 Durability                | 500,000 test cycles                               |                                    |  |
| 5.2.3 Closing moment            | Pass size 2 to 4                                  |                                    |  |
| 5.2.4 Opening moment            | Pass size 2 to 4                                  |                                    |  |
| 5.2.5 Efficiency                | >50% size 2                                       |                                    |  |
| 5.2.5 Efficiency                | >60% size 4                                       |                                    |  |
| 5.2.6 Closing time              | Pass  |                                    |  |
| 5.2.7 Angles of operation       | Grade 3, >105°                                    |                                    |  |
| 5.2.8 Overload performance      | Pass  |                                    |  |
| 5.2.9 Temperature               | -15°C to +40°C                                    | EN 1154:1996/A1:2002/AC:2006       |  |
| dependence                      |   |                                    |  |
| 5.2.10 Fluid leakage            | Pass  |                                    |  |
| 5.2.11 Damage                   | Pass  |                                    |  |
| 5.2.12 Latch control            | Pass  |                                    |  |
| 5.2.13 Back check (optional)    | Pass  |                                    |  |
| 5.2.14 Delayed closing          | NPD   |                                    |  |
| (optional)                      |   |                                    |  |
| 5.2.15 Adjustable closing force | Pass  |                                    |  |
| (optional)                      |   |                                    |  |
| 5.2.16 Zero position (double    | NPD   |                                    |  |
| action door closers only)       |   |                                    |  |
| 5.2.18 Fire/smoke door          | Pass  |                                    |  |
| suitability                     |   |                                    |  |
| Essential characteristics       | Performance                                       | Harmonised technical               |  |
|                                 |   | specification                      |  |
| Durability of Self Closing      |   |                                    |  |
| 5.2.2 Durability                | 500,000 test cycles                               |                                    |  |
| 5.2.17.1 corrosion              | Grade 4 (240 hours)                               |                                    |  |
| 5.2.17.2 corrosion              | Pass  | EN 1154:1996/A1:2002/AC:2006       |  |
| Dangerous Substances            | Pass: the materials in the door closer            |                                    |  |
| Annex ZA3                       | do not contain or release any                     |                                    |  |
|                                 | dangerous substances in excess of                 |                                    |  |
|                                 | the maximum levels specified in                   |                                    |  |
|                                 | existing European material standards              |                                    |  |
|                                 | or any national regulations                       |                                    |  |





# Certificate of constancy of performance 1121-CPR-AD5249

**Produced for** 

## ASSA ABLOY Sicherheitstechnik GmbH Albstadt Works, Bildstockstraße 20, 72458 Albstadt.

and produced in the manufacturing plant

#### X/002

This is coded format and the information is held by the Notified Body.

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

EN 1154:1996/A1:2002/AC:2006

under system 1 of AVCP are applied and that

## the product fulfils all the prescribed requirements set out above.

This certificate was first issued on **18/04/16** and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.

Paul Duggan
Certification Manager
Warrington Certification Ltd

